



## Fittings for metallic conduits

### SC-PC Plain hole connector, IP40

Plain hole connector, nickel plated brass.


#### Features and benefits

- Two part fitting of shell and body without thread
- Acts as a locking device
- The body is fitted to the conduit through the opposite side of the entry
- Provides a smooth entry bush



HelaGuard SC-PC Plain Hole Connector.

<b>MATERIAL</b>	Nickel Plated Brass (NPB)
<b>Operating Temperature</b>	-100 °C to +300 °C



HelaGuard fitting, plain hole connector

TYPE	Nominal Ø	Min. Bore Size (B)	Length (L)	A/F Body (A/F1)	Pack Cont.	Colour	Article-No.
SC10-PC	10	5.6	15.0	13	10 pcs.	Metal (ML)	166-30500
SC12-PC	12	8.5	15.5	17	10 pcs.	Metal (ML)	166-30501
SC16-PC	16	11.5	20.0	20	10 pcs.	Metal (ML)	166-30502
SC20-PC	20	15.3	16.5	24	10 pcs.	Metal (ML)	166-30503
SC25-PC	25	19.1	20.5	29	10 pcs.	Metal (ML)	166-30504
SC32-PC	32	26.2	23.5	38	2 pcs.	Metal (ML)	166-30505
SC40-PC	40	34.2	24.8	48	2 pcs.	Metal (ML)	166-30506
SC50-PC	50	44.8	30.0	58	1 pc.	Metal (ML)	166-30507
SC63-PC	63	54.5	33.5	70	1 pc.	Metal (ML)	166-30508
SC75-PC	75	66.5	42.0	84	1 pc.	Metal (ML)	166-30509

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.